


Place the instruction sticker in the middle above the deposit wheel.





Maintenance

Regularly check whether the drainage holes on the bottom of your KeySecurityBox are open and whether all the bolts are still solid and in place. Treat for possible rust.

Questions?

Ask your supplier, check on www.keysecurityproducts.com or send an email to info@keysecurityproducts.com.

Disclaimer with respect to installation, breakage and theft


The manufacturer and vendor of the KeySecurityBox are not liable for the installation. The installation is easy although we recommend you ask a contractor or other professional to do it for you. The KeySecurityBox is intended for depositing keys and keycards and not for paper and other objects that may get stuck in the deposit wheel. The KeySecurityBox is an anti-theft and anti-breakage box, although with excessive violence theft and breakage are possible. The use is therefore for personal risk and the manufacturer and vendor of the KeySecurityBox are not liable for breakage or theft or physical harm caused by its incorrect use.

© 2012 Holland Commerce

SIMPLE SOLID SAFE



KEYSECURITY SOLID AS A ROCK



www.keysecurityproducts.com

Congratulations on choosing our ultra-reliable KeySecurityBox, the ideal solution for keys and keycards. The KeySecurityBox is extremely durable and, thanks to the range of models, there's always a solution to meet your need.

You have chosen either the KSB 003 (with the deposit wheel on the left) or the 004 (with the deposit wheel on the right). Both are intended for installation on a console. As described below, there are two types of consoles on which you can install your KeySecurityBox 003 or 004. These are the KSB 005 and 006.

NB If need be - ask your local hardware store about the installation material and when drilling always make sure you avoid pipes or wires.

Specifications

Models: KSB 003 and 004 Dimensions: 215 x 355 x 175 mm Weight: 12.3 kg

Colour: RAL 9006

Box content KSB 003 and 004

- 1 x KeySecurityBox
- 1 x floor mat for in the safe
- 4 x Ring ø 50 mm
- 1 x instruction sticker
- 2 x safe key
- 1 x key hanger

Start with console KSB 005 or 006

If you chose console KSB 005, follow instruction numbers 1 and 2.

If you went for console KSB 006, follow instruction numbers 3, 4 and 5.

You will need the following for installation

KSB 005

- At least 100 kg concrete
- 17 mm wrench/spanner
- Spade
- Spirit level
- 2 x steel reinforcing bar (included)

KSB 006


- Pen/pencil
- Anchor bolts or chemical anchors
- Hammer drill with drill
- Wrench/spanner
- Spirit level

Use the key hanger included. It is larger than the hole in the deposit wheel so you cannot throw your keys into the safe by accident.




Installation with console KSB 005

Make a hole in the shape of a pyramid that is at least 50 centimeters deep. Place the steel bars included in the holes in the bottom of the console. Use the spirit level to make sure the console is level and fix it. Dump at least 100 kilograms' concrete according to the specifications of the concrete supplier. Let the concrete harden.









The KSB 006 can be placed on a solid concrete foundation (floor). Draw the drill holes on the floor. Use chemical anchors or anchor bolts (please get some advice from a specialist). Drill holes according to the instructions on the assembly materials. Place the inner bar over the thread ends of the anchors and fix the inner bar with the bolts (make sure it is level).

106 mm

